

**Fisa tehnica**  
**Achizitie trusa scule auto – 2buc**

Caracteristici tehnice minimale pentru **Trusa scule auto**

- (1) -Minim 7 sertare;
- (2) -Minim 160 de piese;
- (3) -Minim Bit Hex 30 mm –H4,H5,H6,H7,H8,H10;H12
- (4) -Minim Bit Hex 75 mm –H4,H5,H6,H7,H8,H10;H12
- (5) -Minim Bit M 30 mm –M5,M6,M7,M10,M12;
- (6) -Minim Bit M 75 mm –M5,M6,M7,M10,M12;
- (7) -Minim Torx 30 mm-T20,T25,T30,T40.T45.T50.T55
- (8) -Minim Torx 75 mm-T20,T25,T30,T40.T45.T50.T55
- (9) -Adaptor Biti: ½",3/8"
- (10) -Minim Chei combinate- 6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,23,24,27,28,30,32;
- (11) -Minim Chei tubulare ½":10,11,12,13,14,15,16,17,18,19,20,21,22,23,24,27,30,32;
- (12) -Antrenor cu clichet ½";
- (13) -Antrenor cu clichet T ½";
- (14) -Prelungitor ½";
- (15) -Articulatie cardanica - ½";
- (16) -Cleste combinat;
- (17) -Cleste taietor
- (18) -Cleste varf ascutit
- (19) -Cleste varf ascutit indoit;
- (20) -Ciocan lacatus minim 300g
- (21) -Ciocan cauciuc
- (22) -Minim 3 dalti
- (23) -Minim 4 surubelnite drepte
- (24) -Minim 9 surubelnite mecanica fina
- (25) -Minim 2 chei reglabile
- (26) -Minim 2 cleste autoblocant
- (27) -Minim 8 tarozi
- (28) -Minim 8 filiere
- (29) -Minim 2 port tarozi
- (30) -Minim 4 clesti seger
- (31) -Minim 5 pile
- (32) -Foarfeca electrician
- (33) -Cutter pliabil
- (34) -Creion tensiune
- (35) -Minim 18 burghie
- (36) -Cleste popnituri
- (37) -Foarfeca tabla